



# Commercial Stainless Steel Freezer / Chiller Product Catalogue



**PT Rotaryana Prima**  
Teuku cik ditiro 16 Jakarta, 10350  
call +6221.310.6767 fax +6221.310.2256  
management@rotaryana.com

f **Rotaryana Prima** @ **Rotaryana**  
<http://www.rotaryana.com/>



We reserve the right to change specifications appearing in this bulletin without incurring any obligation for equipment previously or subsequently sold. Check [www.rotaryana.com](http://www.rotaryana.com) for updates.

# Upright Freezer / Chiller

Delicate design with powerful function.  
An ideal cooling storage partner in your kitchen.

Compressor Applied:

*Danfoss*

NEW

## Internal Fan Compartment Improvement

New fan compartment design maximizes internal storage room of the refrigerator.

NEW

## LED Lighting System

Long life-time, low heat emission LED lighting is installed, with more energy saving.

NEW

## New Design Display Panel

New design rectangular display panel offers a clear platform to demonstrate all operating condition.

NEW

## New Handling

Easy gripping more convenient.



## Optional

Standard come with resin legs, optional interchange with wheels.



Satisfying Usability

A firm durability for professional users. High accurate temperature control by Micro-computer and also seeking after the appearance beauty.

## Auto-Defrost



Before Defrost Process



After Defrost Process

## Built-in Automatic Drainage Evaporator



## LED Lighting System

LED lighting is installed in internal compartment for better vision and make food in / out more easy.



## Dual-Temp, Dual Controller

All Kinco dual-temperature refrigerators are equipped with dual micro-computer controller, which you can easily monitor & control each compartment's temperature and let the machine run as your ideal way.



## Whole Body Foam Insulation Structure

CFC-free Thermal Insulator

Including the partition, the whole body foam insulated to strengthen and improve thermal insulation. Ozone depletion potential (ODP) is zero and CFC-free thermal insulator made with "Cyclopentane" foaming leads to a eco-friendly product.



## Stopper Rack Prevent Overloading

A stopper is installed on the rack to prevent overload, which allows a smooth air circulation inside the refrigerator and maximize cooling performance.



## Thermal Insulated Door-back / Gasket

Improved door-back and gasket enhance thermal insulation performance.



An easy, simple action of maintenance will help to increase the duration of refrigerator life-time.

## Clear Coating Stainless Steel

Clear Coating Stainless Steel is applied on the doors and the front cover. Improved water repellency, oil repellency performance allow user to clean stains from foods, fingerprints on the surface easily.

Improved materials will make it even easier to keep the refrigerator clean and in good hygienic condition.



## Curved Edges Design

All Edges and corners in the compartment are design as curved for easy cleaning.



## Anti-Rusting Treatment



Anti-rusting treatment is applied to the surface of the condenser which prevent rusting due to stored foods.

## Easy-grip Door Handles

Handles are designed for an easy gripping whenever open or close the door.



## Flip-up Front Cover

Flip-up front cover design makes it much more easy to process routine checking or maintenance.



## Air Filter

Air filter protects condenser from dust. The filter is easy to take off / put on whenever cleaning the air filter.

※ Please clean it twice a month for a smooth running.



## Embedded Gasket

Easy for user to install the gasket



Easy Maintenance




**PT Rotaryana Prima**  
Teuku cik ditiro 16 Jakarta, 10350  
call +6221.310.6767 fax +6221.310.2256  
management@rotaryana.com

Facebook: Rotaryana Prima Instagram: Rotaryana  
<http://www.rotaryana.com/>



Upright Freezer  
Upright Refrigerator



Upright Freezer  
Upright Refrigerator



Model	CK-UC70	CK-UF70
Net capacity (L)	589L	
Dimension (mm)	700(w) x 800(d) x 1990(h)	
Electrical supply	880W / 4A	1100W / 5A
Electrical capacity	220-240V . 1Ø 50/60Hz	
Temperature	-6°C to 12°C	-23°C to -7°C



Model	CK-UC140	CK-UF140
Net capacity (L)	1300L	1294L
Dimension (mm)	1400(w) x 800(d) x 1990(h)	
Electrical supply	1100W / 5A	1320W / 6A
Electrical capacity	220-240V . 1Ø 50/60Hz	
Temperature	-6°C to 12°C	-23°C to -7°C



**PT Rotaryana Prima**  
Teuku cik ditiro 16 Jakarta, 10350  
call +6221.310.6767 fax +6221.310.2256  
management@rotaryana.com

Rotaryana Prima    Rotaryana  
<http://www.rotaryana.com/>

We reserve the right to change specifications appearing in this bulletin without incurring any obligation for equipment previously or subsequently sold. **Check [www.rotaryana.com](http://www.rotaryana.com) for updates.**

# Undercounter Freezer / Chiller

Recreated for easy to use with maximum performance

Compressor Applied:

*Danfoss*

NEW

## New Design Display Panel

New design rectangular display panel offers a clear platform to demonstrate all operating condition.

NEW

## New Handling

Easy gripping more convenient.

NEW

## Enhanced Worktop

Enhanced strength of the structure with excellent thermal insulation performance



NEW

## Easy Removeable Air Filter

Air filter protects condenser from dust is allocated just under the front cover, which is easy to take off / put on after cleaning.

NEW

## LED Lighting System

Long life-time, low heat emission LED lighting is installed, with more energy saving.

Easy to Use

Simple, Powerful, Reliable!

## Front Exhaust, Front Intake

Exhaust and intake port are designed on the front. Other equipments can install just next to the refrigerator.



## Auto-Defrost




Before Defrost Process



After Defrost Process

## Top Table Curved Edge Easy to Drain

The curved top table allows drain water off the table much easier without stains the door gasket.



## High Thermal Insulation Performance Door-back / Gasket

With improved door-back and gasket, enhance and maximize the level of thermal insulation.



## LED Lighting System

LED lighting is installed in internal compartment for better vision and make food in / out more easy.



Designed to easily clean or maintain the machine.

## Clear Coating Stainless Steel

Clear Coating Stainless Steel is applied on the doors and the front cover. Improved water repellency, oil repellency performance allow user to clean stains from foods, fingerprints on the surface easily.

Improved materials will make it even easier to keep the refrigerator clean and in good hygienic condition.



## Micro-computer Controlled & Digital Display

Adapted Micro-computer control method that can set the temperature in 1 degree celsius increments depends on storage items.



Easy Maintenance

## Optional Wheels for Easy Movement

### Optional

Standard come with resin legs, optional interchange with wheels.



## Easy-grip Door Handles

New designed handles are designed for an easy gripping whenever open or close the door.



## Easy to Replace Gasket

Inlay type design for easy installation.



## Curved Edges Design

All Edges and corners in the compartment are design as curved for easy cleaning.



## Refrigerant Gas Filling Port

Installed port is highly convenient for maintenance activities, e.g. checking the volume of refrigerant gas; or filling refrigerant; and collecting stored gas whenever needed.




**PT Rotaryana Prima**  
Teuku cik ditiro 16 Jakarta, 10350  
call +6221.310.6767 fax +6221.310.2256  
management@rotaryana.com

Rotaryana Prima @ Rotaryana  
<http://www.rotaryana.com/>





## Counter Freezer Counter Refrigerator



## Counter Freezer Counter Refrigerator



### 600MM Depth (CK-CC-XX-60 / CK-CF-XX-60)



Model	CK-CC90-75	CK-CF90-75
Net capacity (L)	180L	
Dimension (mm)	900(w) x 750(d) x 800(h)	
Electrical supply	616W / 2.8A	770W / 3.5A
Electrical capacity	220-240V . 1Ø 50/60Hz	
Temperature	-6°C to 12°C	-23°C to -7°C

### 750MM Depth (CK-CC-XX-75 / CK-CF-XX-75)



Model	CK-CC150-60	CK-CF150-60
Net capacity (L)	302L	
Dimension (mm)	1500(w) x 600(d) x 800(h)	
Electrical supply	660W / 3A	880W / 4A
Electrical capacity	220-240V . 1Ø 50/60Hz	
Temperature	-6°C to 12°C	-23°C to -7°C



Model	CK-CC120-60	CK-CF120-60
Net capacity (L)	218L	
Dimension (mm)	1200(w) x 600(d) x 800(h)	
Electrical supply	660W / 3A	880W / 4A
Electrical capacity	220-240V . 1Ø 50/60Hz	
Temperature	-6°C to 12°C	-23°C to -7°C



Model	CK-CC150-75	CK-CF150-75
Net capacity (L)	401L	
Dimension (mm)	1500(w) x 750(d) x 800(h)	
Electrical supply	660W / 3A	880W / 4A
Electrical capacity	220-240V . 1Ø 50/60Hz	
Temperature	-6°C to 12°C	-23°C to -7°C



Model	CK-CC120-75	CK-CF120-75
Net capacity (L)	290L	
Dimension (mm)	1200(w) x 750(d) x 800(h)	
Electrical supply	660W / 3A	880W / 4A
Electrical capacity	220-240V . 1Ø 50/60Hz	
Temperature	-6°C to 12°C	-23°C to -7°C



Model	CK-CC180-75	CK-CF180-75
Net capacity (L)	514L	
Dimension (mm)	1800(w) x 750(d) x 800(h)	
Electrical supply	660W / 3A	1100W / 5A
Electrical capacity	220-240V . 1Ø 50/60Hz	
Temperature	-6°C to 12°C	-23°C to -7°C




**PT Rotaryana Prima**  
Teuku cik ditiro 16 Jakarta, 10350  
call +6221.310.6767 fax +6221.310.2256  
management@rotaryana.com

Rotaryana Prima @ Rotaryana  
<http://www.rotaryana.com/>

We reserve the right to change specifications appearing in this bulletin without incurring any obligation for equipment previously or subsequently sold. **Check [www.rotaryana.com](http://www.rotaryana.com) for updates.**



## Counter Drawer Freezer / Counter Drawer Refrigerator



## Counter Drawer Freezer / Counter Drawer Refrigerator



Model	<b>CK-CC140-75-L4D</b>
Net capacity (L)	167L
Dimension (mm)	1400(w) x 750(d) x 570(h)
Electrical supply	660W / 3A
Electrical capacity	220-240V . 1Ø 50/60Hz
Temperature	-6°C to 12°C



Model	<b>CK-CC-150-75-4D</b>
Net capacity (L)	400L
Dimension (mm)	1500(w) x 750(d) x 800(h)
Electrical supply	660W / 3A
Electrical capacity	220-240V . 1Ø 50/60Hz
Temperature	-6°C to 12°C



Model	<b>CK-CC-120-75-4D</b>
Net capacity (L)	280L
Dimension (mm)	1200(w) x 750(d) x 800(h)
Electrical supply	660W / 3A
Electrical capacity	220-240V . 1Ø 50/60Hz
Temperature	-6°C to 12°C



Model	<b>CK-CC-180-75-6D</b>
Net capacity (L)	500L
Dimension (mm)	1800(w) x 750(d) x 800(h)
Electrical supply	660W / 3A
Electrical capacity	220-240V . 1Ø 50/60Hz
Temperature	-6°C to 12°C



**PT Rotaryana Prima**  
Teuku cik ditiro 16 Jakarta, 10350  
call +6221.310.6767 fax +6221.310.2256  
management@rotaryana.com

Rotaryana Prima   Rotaryana  
<http://www.rotaryana.com/>

We reserve the right to change specifications appearing in this bulletin without incurring any obligation for equipment previously or subsequently sold. **Check [www.rotaryana.com](http://www.rotaryana.com) for updates.**