

BLAST FREEZER FOR RESTAURANT & BAKERY

Blast Chiller/Shock Freezer for 5GN 1/1 **BCB/05**

Dim (cm): 80x70x90
Shelves/Trays: 5 GN 1/1 / 5 EN (60x40)
Trays pitch : 67
Yield :
+90/+3°C = 15 Kg
v+90/-18°C = 10 Kg
Cooling power : 780
Gas : R452A
Input voltage :
1x230V - 50Hz
Climatic class : 5



Blast Chiller/Shock Freezer for 5GN 1/1 **BCB/10**

Dim (cm): 80x78x170
Shelves/Trays: 10 GN 1/1 / 10 EN (60x40)
Trays pitch : 67
Yield :
+90/+3°C = 34 Kg
+90/-18°C = 22 Kg
Cooling power : 1885
Gas : R452A
Input voltage :
1x230V - 50Hz
Climatic class : 5



Blast Chiller/Shock Freezer for 5GN 1/1 **BCB/15**

Dim (cm): 80x78x200
Shelves/Trays: 15 GN 1/1 / 15 EN (60x40)
Trays pitch : 67
Yield :
+90/+3°C = 50 Kg
+90/-18°C = 38 Kg
Cooling power : 2710
Gas : R452A
Input voltage :
3x400V - 50Hz
Climatic class : 5



Blast Chiller/Shock Freezer for 5GN 1/1 **BCT/05**

Dim (cm): 80x72x90
Shelves/Trays: 5 GN 1/1 / 5 EN (60x40)
Trays pitch : 67
Yield :
+90/+3°C = 26 Kg
v+90/-18°C = 16 Kg
Cooling power : 1095
Gas : R452A
Input voltage :
1x230V - 50Hz
Climatic class : 5



Blast Chiller/Shock Freezer for 5GN 1/1 **BCT/10**

Dim (cm): 80x80x170
Shelves/Trays: 10 GN 1/1 / 10 EN (60x40)
Trays pitch : 67
Yield :
+90/+3°C = 43 Kg
+90/-18°C = 32 Kg
Cooling power : 2710
Gas : R452A
Input voltage :
3x400V - 50Hz
Climatic class : 5



Blast Chiller/Shock Freezer for 5GN 1/1 **BCT/15**

Dim (cm): 80x80x200
Shelves/Trays: 15 GN 1/1 / 15 EN (60x40)
Trays pitch : 67
Yield :
+90/+3°C = 70 Kg
+90/-18°C = 55 Kg
Cooling power : 3360
Gas : R452A
Input voltage :
3x400V - 50Hz
Climatic class : 5



PT Rotaryana Prima
Teuku cik ditiro 16 Jakarta, 10350
call +6221.310.6767 fax +6221.310.2256
customer.service@rotaryana.com

f **Rotaryana Prima** @ **Rotaryana**
<http://www.rotaryana.com/>



RETARDER PROVER

Retarder Prover Cabinet 40 Trays **AFLV/20**

Dim (mm) : 790x690x2140
Insulation thickness (mm) : 75
Capacity : 500 lt
Doors : 1
Trays capacity : 20 600x400
Temperature (°C) : -10/+35
Max power (W) : 1250
Refrigerated power (W) : 675
Gas : R290
Input voltage : 1x230V/50Hz
Climate class : 5



Retarder Prover Cabinet 40 Trays **AFLV/40**

Dim (mm) : 790x1080x2140
Insulation thickness (mm) : 75
Capacity : 900 lt
Doors : 1
Trays capacity : 40 600x400
Temperature (°C) : -10/+35
Max power (W) : 1785
Refrigerated power (W) : 1063
Gas : R290
Input voltage : 1x230V/50Hz
Climate class : 5



PT Rotaryana Prima
Teuku cik ditiro 16 Jakarta, 10350
call +6221.310.6767 fax +6221.310.2256
customer.service@rotaryana.com

f **Rotaryana Prima** @ **Rotaryana**
<http://www.rotaryana.com/>

